




Fiber Optics vis-NIR Spectrophotometer for Transmission measurements

Model: VS-T



VS-T system include:

Item	Description	Number
1	vis-NIR spectrometer (300-1100 nm)	1
2	Halogen-Tungsten Light Source (300-2500 nm)	1
3	2-side Cuvette Holder with quartz lenses	1
4	Armored, 600um core, Solarization Resistant fiber optic cable	2

Features:

- Transmittance and Absorbance Spectrometer
- Vis-NIR Detection Wavelength Range from 300-1100 nm (Custom design with 660 nm spectral range)
- Detachable optics assembly suitable for portable process, and lab applications
- From 1 µs to 4 seconds CCD Integration time
- Aberration- Corrected Concave Holographic Grating
- High speed USB-2 interface
- Ruggedized Aluminum Enclosure

• Fiber Optics cables with SMA 905 input fiber connectors for interfacing with other equipment such as light sources and sample holders.

Simultaneous Spectrophotometer and Colorimeter

VS-T can be used as a vis-NIR spectrophotometer to measure transmission and absorbance of liquids and transparent materials as well as a colorimeter to determine the CIE (L^* , a^* , b^*) and XYZ parameters of colors in the visible range.

It's a modular spectrometer that can acquire a full spectrum in less than 1 millisecond with 0.25 nm step.

Applications:

- Material science
- Life Science
- Food Science
- Earth Science
- Painting and more...

UVS-spec[®] software

- Free real-time operating software
- Compatible with Windows 10
- Dark-level correction
- Thermal Smoothing
- Finding Peaks
- CIE measurements
- Real-time variation measurements
- Calculating ratio of two wavelengths intensities

Specifications

Operating Mode	Transmittance, Absorbance	
Wavelength Range	300-1100 nm custom products (spectral range: 660nm)	
Wavelength steps	0.25 nm	
Resolution	0.7 nm	
Wavelength Reproducibility	± 0.1 nm	
Detector	CCD 3648 Pixels	
Light Source	Halogen-Tungsten	
Stray Light	< 0.2 %T	
Photometric Measuring Range	0-3 Abs	
User Interface Language	English	
Interface	USB2	
Power	220 V AC	
Dimensions (H x W x D)	155mm*140mm*65mm	
Weight	< 2 kg	
Data saving	EXCEL, PTS	

Contact us:

No.002, Rouyesh Bld., Niroo Research Institute, At The End of Shahid Dadman Blvd., Shahrak Ghods, TEHRAN, IRAN

www.phystec.ir

Telefax: +98-2188364614

info@phystec.ir